



# XB - Series

# NEWTEC

model 2008XB/2009XB/  
2012XB/2014XB

the world leaders

## multi-head weigher



## high output, low giveaway

- Available with 8, 9, 12 or 14 channels
- Robustly constructed in stainless steel
- Gentle product handling with low drops
- Accuracy and speed combined
- Operator friendly
- Capable of running with more than one channel disabled
- Low cost of ownership
- Premium reliability



# NEWTEC

the world leaders

## XB - Series

model 2008XB/2009XB/  
2012XB/2014XB

NEWTEC A/S  
Stærmosegårdsvej 18  
DK-5230 Odense M  
Denmark

T: +45 66 15 84 44  
F: +45 66 15 44 39

E: mail@newtec.dk  
www.newtec.com

**Capacity** Portions per minute up to  
Estimated capacity tested on potatoes.

Model	2008XB	2009XB	2012XB	2014XB
1 kg	37	38	60**	-
Giveaway	4g	2g	7g	-
2.5 kg	34	35	55**	55**
Giveaway	8g	4g	10g	10g
5 kg	27	28	46**	46**
Giveaway	21g	12g	28g	20g
10 kg	19	20	21	22
Giveaway	44g	20g	4g	4g
12.5 kg	17	18	20	21
Giveaway	62g	25g	7g	7g
15 kg	12*	15	18	19
Giveaway	20g	32g	8g	8g
20 kg	11*	11*	15	16
Giveaway	24g	17g	9g	9g
25 kg	9*	10*	14	15
Giveaway	40g	18g	12g	12g

\*2 dumps  
\*\*the machine runs as two 8/9 channel machines

## For potatoes and onions

- Simply cleaned
- Pack weight programming in seconds
- Fully automatic infeed control
- Automatic taring
- Automatically controlled feeding system
- 8 and 9 head multi dump facility for up to 25kg portions

## Technical Data

Air requirement: Min. pressure: 7 Bar/100 psi  
Consumption: 150 - 200 l/min

Electrical requirement: 230/380 V+N+PE

## Optional

- Automatic anti-bridging system in vibrator feed
- Large infeed hopper
- Extra large weigh pans

